

Rec'd PCT/PTO 17 MAR 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number
WO 2004/027207 A1

(51) International Patent Classification⁷: E21B 17/10,
B21D 26/02

(74) Agent: BENNETT JONES LLP; Attention: Roseann
Caldwell, 4500 Bankers Hall East, 855 - 2nd Street SW,
Calgary, Alberta T2P 4K7 (CA).

(21) International Application Number:
PCT/CA2003/001392

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date:
23 September 2003 (23.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2,404,577 23 September 2002 (23.09.2002) CA

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): TESCO
CORPORATION [CA/CA]; 6204 - 6A Street SE, Calgary,
Alberta T2H 2B7 (CA).

(72) Inventor; and


(75) Inventor/Applicant (*for US only*): SLACK, Maurice,
William [CA/CA]; 4628 Eleniak Road, Edmonton, Al-
berta T6B 2S1 (CA).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

[Continued on next page]

(54) Title: PIPE CENTRALIZER AND METHOD OF FORMING



(57) Abstract: A centralizer for installing on a metal pipe. The centralizer includes a generally tubular body having a central opening sufficiently large to allow insertion therethrough of a pipe having an external diameter; a sidewall of substantially uniform thickness including an inner-facing surface directed to the central opening and an outer-facing surface onto which are formed a plurality of outwardly protruding ribs by hydroforming the sidewall. A method for hydroforming a centralizer including placing a length of metal tubular work piece, the work piece having a sidewall and a central opening, inside a confining surface comprised of mold elements,

the mold elements including cavities spaced and shaped in the configuration of desired side wall centralizer ribs, the mold elements being supported substantially against expansion radially outward from their position about the tubular work piece; applying sufficient pressure to the side wall through the inner bore to force the tubular sidewall radially outward against the confining surface and into the mold cavities to plastically deform the side wall to form centralizer ribs on the side wall; and removing the tubular work piece from the confining surface.

WO 2004/027207 A1